

QDLASER

QLD1261-4005

1240 nm DFB Laser Butterfly Package

Preliminary

C00072-03 Oct. 2013



1. DESCRIPTION

The QLD1261 is a 1240-nm distributed feedback (DFB) laser. The laser is assembled into a 14-pin butterfly package with an optical isolator, a monitor PD and a thermo-electric cooler.

2. FEATURES

- Single longitudinal mode operation at 1240 nm
- Fiber-pigtailed 14-pin butterfly package with a TEC
- Optical isolator integration
- Polarization maintaining fiber integration

3. APPLICATIONS

- Test and measurement
- Sensing

4. ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATING	UNIT
Optical Output power	P_f	20	mW
LD Forward Current	I_f	150	mA
LD Reverse Voltage	V_{RLD}	2	V
TEC Drive Current	I_{TEC}	2	A
TEC Drive Voltage	V_{TEC}	4.3	V
Operation Temperature	T_c	0 to 60	°C
Storage Temperature	T_{stg}	-40 to 85	°C
Lead Soldering Temperature (5 s)	T_{sld}	230	°C

5. OPTICAL AND ELECTRICAL CHARACTERISTICS


($T_{LD} = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Peak Wavelength	λ_p	CW, $P_f=5$ mW	1235	1240	1245	nm
Fiber Output Power	P_f	CW, $I_f=100$ mA	5	-	-	mW
Threshold Current	I_{th}	CW	-	7	-	mA
Operation Current	I_{op}	CW, $P_f=5$ mW	-	60	150	mA
Operation Voltage	V_{op}	CW, $P_f=5$ mW	-	1.6	2.5	V
Sidemode Suppression Ratio	SMSR	CW, $P_f=5$ mW	-	40	-	dB
Polarization Extinction Ratio	PER	CW, $P_f=5$ mW	15	20	-	dB
Fiber cutoff wavelength	-	-	-	0.9	-	μm
Thermistor Resistance	Rth	$T_{LD} = 25^\circ\text{C}$, B=3930K	9.5	10	10.5	k Ω

distributed by

1 / 2


6. OUTLINE DRAWING AND PIN CONFIGURATION



All dimensions in millimeters.

7. PIN CONFIGURATION

No.	Description	No.	Description
1	TEC (+)	8	NC
2	Thermistor	9	NC
3	PD Anode	10	Laser Anode
4	PD Cathode	11	Laser Cathode
5	Thermistor	12	NC
6	NC	13	Case Ground
7	NC	14	TEC (-)



8. NOTICE

- Safety Information

This product is classified as Class 3B laser product, and complies with 21 CFR Part 1040.10.

Please do not take a look at laser lighting in operations since laser devices may cause troubles to human eyes.

Please do not eat, burn, break and make chemical process of the products since they contain GaAs material.

- Handling products

Semiconductor lasers are easily damaged by external stress such as excess temperature and ESD. Please pay attention to handling products, and use within range of maximum ratings. QD Laser takes no responsibility for any failure or unusual operation resulting from improper handling, or unusual physical or electrical stress.

- RoHS

This product conforms to RoHS compliance related EU Directive 2002/95/EC.

QD Laser, Inc.

Contact : info@qdlaser.com <http://www.qdlaser.com>

Copyright 2012 All Rights Reserved by QD Laser, Inc.

Keihin Bldg. 1F 1-1 Minamiwatarida-cho, Kawasaki-ku, Kawasaki, Kanagawa Zip 210-0855 Japan

All company or product names mentioned herein are trademarks or registered trademarks of their respective owners. Information provided in this data sheet is accurate at time of publication and is subject to change without advance notice.